



## Legrand

Tamper-Resistant Heavy-Duty Decorator Spec Grade Single Receptacle, Ivory  
Part No. TR263611



Tamper-Resistant Heavy-Duty Decorator Spec Grade Single Receptacle, Back & Side Wire, 20amp 125volt, Brown  
For detailed Tamper-Resistant receptacle information, visit our Tamper-Resistant Receptacles page.

### Features & Benefits

Dual mechanical shutter system to help prevent insertion of foreign objects.

Easily accessed break-off line-contact connecting tab for fast and easy split-circuit wiring.

Internal screw-pressure-plate back and side wire capability.

Corrosion-resistant plated steel strap is locked in to face and back body to resist pulling away from the face/body assembly.

Two drive screws anchor steel strap to back body and face where abrupt removal torque is greatest.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click [here](#).

Auto-ground clip assures positive ground.

Backed-out tri-drive brass terminal screws for faster installation.

Two back wire holes for additional wiring flexibility.

.032 inch thick brass triple-wipe power contacts.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

### Specifications

#### General Info

UPC Number 785007005011

Countries Of Origin Mexico

Product Line Pass & Seymour

Application Sector Commercial

Standard UL498, CSA C22.2 No. 42

#### Listing Agencies / 3rd Party Agencies

cULus Listed Yes

#### Technical Information

Number of Poles Double Pole

Voltage 125 V

Connection Back and side wire

---

**Dielectric Strength** Withstands 2000V minimum

---

**Temperature Rating** Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

---

**Wire Size** #14 - #10

---

**Number of Wires** 3

---

**Environmental Conditions** Flammability: UL94 V2

---