



Tamper-Resistant Spec Grade Receptacles, Back and Side-Wire, 15A, 125A



Features & Benefits

- | | |
|---|--|
| Thermoplastic dual mechanism shutter system to help prevent insertion of foreign objects. | Exclusive patented feature, circuit label on face allows permanent circuit identification. |
| Extra heavy-duty brass, one-piece mounting strap with integral ground. | One-piece, brass, triple-wipe power contacts for lasting retention. |
| Strap tabs wrap around and lock down on face to prevent strap from separating from face and back body. | Impact-resistant nylon face and back body. |
| Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring. | Two drive screws anchor strap to back body and face. |
| Exclusive patented feature, external screw-pressure-plate back wire clamp on ground terminal for faster, easier installation. | External screw-pressure-plate back wire clamps with #10 brass terminal screws for visual assurance of a good connection. |
| Auto-ground clip assures positive ground. | For covering patents, see www.legrand.us/patents . |
| For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here . | Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact |

Specifications

General Info

| | | | |
|-------------------|----------------|--------------------|------------|
| Product Line | Pass & Seymour | Color | Gray |
| Country Of Origin | Mexico | Application Sector | Commercial |
| Standard | UL 498 | | |

Dimensions

| | | | |
|-------------------|----------|------------------|--------|
| Product Width US | 1.625 in | Product Depth US | 0.9 in |
| Product Height US | 2.75 in | | |

Listing Agencies / 3rd Party Agencies

| | | | |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 140596 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

Technical Information

| | | | |
|---------------------|-------------|-----------|-------------|
| Is Tamper-Resistant | Yes | Phase | 3 |
| Number of Wires | 3 | Amperage | 15 A |
| Number of Poles | Double Pole | Wire Size | 14 - 10 AWG |
| Voltage | 125.0 V | | |
