



5' Plugmold Multioutlet System with 10 single outlets.

## Features & Benefits

Steel Raceway. Provides superior strength for any dry location installation.

Available in Ivory ScuffCoat or gray baked enamel finish. The durable ScuffCoat provides a durable, scratch-resistant finish while the gray baked enamel compliments the décor or can be painted.

Single-and-dual-gang boxes. Wire devices into the raceway system or protect a Plugmold® strip with a surge or GFCI device.

Single, alternating circuit, and isolated ground receptacles. Meets virtually any job requirement.

Snapicoil harnesses of prewired receptacles in 48' and 50'. Eliminates multiple splicing, speeding up installation on long runs.

Customization available. All products can be modified to accommodate virtually any application.

Compact, low profile appearance. Requires minimal space.

Full range of fittings. Provides a complete wiring solution.

Factory wired Plugmold® sections available in 3', 5', and 6' lengths with 15A receptacles installed in cover. Ideal for short runs requiring additional outlets in electrically busy areas.

Choice of receptacle spacing. Center spacing between receptacles of 6", 9", 12", and 18".

Snapicoil harnesses offer a choice of receptacle spacing. Center spacing between receptacles of 12", 18" and 30".

This product meets the material restrictions of RoHS.

## Specifications

### General Info

|              |              |                       |               |
|--------------|--------------|-----------------------|---------------|
| UPC Number   | 786776074505 | Country Of Origin     | United States |
| Product Line | Wiremold     | Application Sector    | Commercial    |
| Type         | Plugmold     | Number of Receptacles | 10            |

---

Standard

cULus Listed Base & Blank Cover: File E4376 Guide RJBT. Multioutlet Assemblies: File E15191 Guide PVGT. Fittings: File E41751 Guide RJPR. Base & Blank Cover & Plugmold Series w/Snapcoil Harness: Meets Article 386 of NEC. Meets Section 12-3032 of CEC. Plugmold Wired Sections: Meets Article 380 of NEC. Meets Section 12-3032 of CEC.

---

**Listing Agencies / 3rd Party Agencies**

---

|              |     |                     |        |
|--------------|-----|---------------------|--------|
| cULus Listed | Yes | cULus ListingNumber | E15191 |
|--------------|-----|---------------------|--------|

---

**Buy American Act Compliance**

---

|       |     |
|-------|-----|
| NAFTA | Yes |
|-------|-----|

---

**Additional Information**

---

|                 |     |                               |     |
|-----------------|-----|-------------------------------|-----|
| RoHS Conformant | Yes | Product Environmental Profile | Yes |
|-----------------|-----|-------------------------------|-----|

---

**Technical Information**

---

|         |       |                |       |
|---------|-------|----------------|-------|
| Voltage | 125 V | Enclosure Type | Steel |
|---------|-------|----------------|-------|

---

|                          |                        |
|--------------------------|------------------------|
| Environmental Conditions | Dry interior locations |
|--------------------------|------------------------|

---