



### LEGRAND'S ENVIRONMENTAL COMMITMENTS

- Incorporate environmental management into our industrial sites  
 Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).
- Offer our customers environmentally friendly solutions  
 Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.
- Involve the environment in product design and provide informations in compliance with ISO 14025  
 Reduce the environmental impact of products over their whole life cycle.  
 Provide our customers with all relevant information (composition, consumption, end of life, etc.).

For more information on Legrand's PEPs and other sustainability initiatives, visit [www.legrand.us/about-us/csr/circular-economy](http://www.legrand.us/about-us/csr/circular-economy)



### REFERENCE PRODUCT

Function	Accommodate and protect the wiring and wiring accessories along 1 metre for a Reference Service Life of the product of 20 years. The installation system with cross-section of 9900 mm <sup>2</sup> includes the profile and accessories that are representative of standard use.
Reference Product	<div style="text-align: center;"> </div> <p>Part Number: 6000 Series Raceway System (Base, Cover, Fittings, and Device Plates)                  Wiremold Two-Piece Surface Steel Raceway</p>



### PRODUCTS CONCERNED

The environmental data is representative of the Wiremold 6000 Series Steel Raceway system in either Gray or Ivory (starting PN of G or V). A standard system product list was chosen by selecting the components of each accessory type with the highest environmental impact across all categories. As a result, the following parts were modeled to represent this system:

- |   |  |
|---|--|
| <p>6000 SERIES:</p> <ul style="list-style-type: none"> <li>-G6000B-10</li> <li>-G6000C</li> <li>-G6001DA</li> <li>-G6017TX</li> <li>-GG6011TX</li> <li>-6001A</li> <li>-G6010B</li> <li>-G4047AX</li> <li>-G4047-2BBXX</li> </ul> | <p>4000 SERIES:</p> <ul style="list-style-type: none"> <li>-G4000B-10</li> <li>-G4000C</li> <li>-4001DA</li> <li>-G4018</li> <li>-G4011FO</li> <li>-G4015DFO</li> <li>-G4010DFO</li> <li>-G4047AX</li> <li>-G4047-2BBXX</li> </ul> |
|---|--|

# Product Environmental Profile

## Wiremold® 4000 & 6000 Series Steel Raceway Systems



The following additional parts were not modeled, but are included in this section as similar accessories with lesser impact than the parts chosen within the modeled system:

-G4000C075, G4000C135, G4000C195, G4000C315, G6012TX, G4017TCA, G4017, G4017N, G4018FO, 4017/18R, G4017FO, G4011, G4015D, G4015, 4015DRI, G4010B, GG4047BB, G4047C-1, G4047C-2, G4047JX, G4047BF, G4047RX, G4047BM, G4047BS, G4047RF, G4047BT, G4047WX, G4047-2BBBB, G4047-2BBFF, G4047-2BBMM, G4047-2BBSS, G4047-2BBTT, G4047-2RRXX



### CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU amended by delegated directive (EU) 2015/863, and its amendment 2017/2102/EU.

Total weight of Reference Product	5.31 kg				
Plastics as % of weight	Metals as % of weight		Others as % of weight		
Product only: 4.93 kg					
	Steel	91.5 %	Coating Paint	1.4 %	
Packaging only: 0.38 kg					
PE (Packaging)	0.1 %		Wood (Pallet)	< 0.1 %	
			Cardboard (Packaging)	5.7 %	
			Paper (Packaging)	1.3 %	
Total plastics	0.1 %	Total metals	91.5 %	Total others	8.4 %

Recycled material content: 56 % by weight of Reference Product

- Product only : 55 %
- Packaging only: 64 %



### MANUFACTURING

This Reference Product comes from sites that have received ISO14001 certification. The final assembly location is West Hartford, CT.



### DISTRIBUTION

Products are distributed from logistics centers located to optimize transport efficiency using EPA SmartWay® certified carriers to reduce greenhouse gases emissions. Information on the distance of distribution is not available so the PCR hypothesis for "Intracontinental transport", 2175 miles (3500 km) by heavy truck, was used. This represents transportation of the Reference Product from our warehouse to the local point of distribution in the North American market.



### INSTALLATION

For the installation of the product, only standard tools are required. No electricity usage was taken into account.



### USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.

# Product Environmental Profile

## Wiremold® 4000 & 6000 Series Steel Raceway Systems



### END OF LIFE

The product end of life is taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or, failing that, another form of reuse.



### ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end of life. It is representative of products marketed and used in North America. The dataset used in this PEP is representative of the year 2024.

For each stage, the following modelling elements were taken into account at each life cycle stage (and module):

System Boundary	Manufacturing (A1-A3)	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing. Energy Model: Electricity Mix_Low voltage_2020_United States_US
	Distribution (A4)	Transport between the last distribution center and an average delivery point in the sales area.
	Installation (A5)	The end of life of the packaging.
	Use (B1-B7)	<ul style="list-style-type: none"> <li>Product category: Installation cable trunking or mini-trunking and skirting systems</li> <li>Use scenario: No energy consumption during the 20 years working life. This modelling duration does not constitute a minimum durability requirement.</li> <li>Energy model: None</li> </ul>
	End of life (C1-C4)	The default end of life scenario modelled maximizes the environmental impact using the PCR hypothesis for "Local transport": 621 miles (1000 km) by heavy truck and landfilling.
Benefits & Loads (Module D)	Module D is calculated according to PCR-ed4-EN-2021 09 06 based on the materials recycled and the modelled end-of-life scenario. It expresses the net benefits and loads beyond the boundaries of the system, and are not to be included in the life cycle totals.	
Software and data-base used	EIME V6 and its CODDE-2024 database	

For each stage, the energy mix modelled is based on default information integrated in the data modules used from the aforementioned database unless otherwise indicated.

# Product Environmental Profile

## Wiremold® 4000 & 6000 Series Steel Raceway Systems




### ENVIRONMENTAL IMPACTS

Environmental Impact Indicators		Total Life Cycle Impacts		Manufacturing	Distribution	Installation	Use	End of Life	Benefits & Loads
				A1-A3	A4	A5	B1-B7	C1-C4	Module D
Climate change - total	GWP	4.60E+01	kg CO <sub>2</sub> eq	3.33E+01	9.38E-01	7.19E-01	0.00E+00	1.11E+01	-4.75E+00
Climate change - fossil fuels	GWPf	4.59E+01	kg CO <sub>2</sub> eq	3.37E+01	9.38E-01	1.30E-01	0.00E+00	1.11E+01	-4.41E+00
Climate change - biogenics	GWPb	1.67E-01	kg CO <sub>2</sub> eq	-4.24E-01	0.00E+00	5.89E-01	0.00E+00	1.92E-03	-3.43E-01
Climate change - land use and land use transformation	GWPlu	0.00E+00	kg CO <sub>2</sub> eq	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Ozone depletion	ODP	9.96E-07	kg CFC-11 eq	9.05E-07	1.44E-09	4.69E-09	0.00E+00	8.45E-08	9.25E-09
Acidification	AP	1.99E-01	mole of H+ eq	1.51E-01	5.95E-03	7.90E-04	0.00E+00	4.09E-02	-1.45E-02
Eutrophication, freshwater	Epf	6.56E-05	kg P eq	6.27E-05	3.52E-07	1.02E-07	0.00E+00	2.50E-06	3.88E-06
Eutrophication, marine aquatic	Epm	4.26E-02	kg of N eq	3.20E-02	2.79E-03	1.92E-04	0.00E+00	7.62E-03	-2.23E-03
Eutrophication, terrestrial	Ept	4.92E-01	mole of N eq	3.73E-01	3.06E-02	2.52E-03	0.00E+00	8.52E-02	-2.57E-02
Photochemical ozone formation	POCP	1.49E-01	kg NMVOC eq	1.11E-01	7.72E-03	5.41E-04	0.00E+00	2.94E-02	-1.02E-02
Abiotic resource depletion - elements	ADPe	6.23E-04	kg Sb eq	6.23E-04	0*	0*	0.00E+00	4.60E-07	-1.59E-07
Abiotic resource depletion - fossil fuels	ADPf	1.67E+03	MJ	8.26E+02	1.31E+01	2.41E+00	0.00E+00	8.28E+02	-3.72E+02
Water use	WU	3.04E+01	m <sup>3</sup> world eq	2.61E+01	3.57E-03	5.54E-03	0.00E+00	4.29E+00	-1.87E+00

The values of the indicators defined in the PCR-ed4-EN-2021 09 06 are available in the digital database of pep-ecopassport.org website.

The environmental impact of the Reference Product is most significant during the manufacturing stage.



# Product Environmental Profile

## Wiremold® 4000 & 6000 Series Steel Raceway Systems



### ENVIRONMENTAL IMPACTS

Inventory Flow Indicators		Total Life Cycle Impacts		Manufacturing	Distribution	Installation	Use	End of Life	Benefits & Loads
				A1-A3	A4	A5	B1-B7	C1-C4	Module D
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	ERP	2.13E+01	MJ	2.05E+01	1.75E-02	1.81E-01	0.00E+00	5.74E-01	-1.00E+00
Use of renewable primary energy resources used as raw materials	ERM	6.72E+00	MJ	6.72E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.36E+00
Total use of renewable primary energy resources	ER	2.80E+01	MJ	2.73E+01	1.75E-02	1.81E-01	0.00E+00	5.74E-01	3.35E+00
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	ENRP	1.67E+03	MJ	8.24E+02	1.31E+01	2.41E+00	0.00E+00	8.28E+02	-3.72E+02
Use of non-renewable primary energy resources used as raw materials	ENRM	1.93E+00	MJ	1.93E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total use of non-renewable primary energy resources	ENR	1.67E+03	MJ	8.26E+02	1.31E+01	2.41E+00	0.00E+00	8.28E+02	-3.72E+02
Use of secondary materials	USM	3.84E+00	kg	3.84E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of renewable secondary fuels	URSF	0.00E+00	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of non-renewable secondary fuels	UNRSF	0.00E+00	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Net use of fresh water	NUFW	7.08E-01	m <sup>3</sup>	6.08E-01	8.31E-05	2.17E-04	0.00E+00	1.00E-01	-4.36E-02
Hazardous waste disposed	HWD	8.96E+00	kg	3.09E+00	0.00E+00	1.40E-01	0.00E+00	5.73E+00	9.08E-03
Non-hazardous waste disposed	NHWD	2.24E+01	kg	2.23E+01	3.30E-02	1.90E-02	0.00E+00	9.31E-02	1.81E-01
Radioactive waste disposed	RWD	1.14E-02	kg	1.13E-02	2.35E-05	7.82E-06	0.00E+00	6.27E-05	8.27E-05
Components for re-use	CRU	0.00E+00	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	MRE	5.13E+00	kg	1.24E+00	0.00E+00	0.00E+00	0.00E+00	3.89E+00	0.00E+00
Materials for energy recovery	MER	0.00E+00	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	EE	0.00E+00	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content of the product	BCpdt	0.00E+00	kg C						
Biogenic carbon content of the associated packaging	BCpkg	2.58E-01	kg C						

In accordance with the PCR, the "Benefits & Loads" are beyond the system boundary and are thus not included in the results of "Total Life Cycle Impacts".

The values of the indicators defined in the PCR-ed4-EN-2021 09 06 are available in the digital database of [pep-ecopassport.org](http://pep-ecopassport.org) website.

\*Represents less than 0.01% of the total life cycle of the reference flow.

# Product Environmental Profile

## Wiremold® 4000 & 6000 Series Steel Raceway Systems



### ENVIRONMENTAL IMPACTS

The following additional systems were modelled:

	Manufacturing	Distribution	Installation	Use	End of Life	Module D
6000 Series Raceway	1.0	1.0	1.0	1.0	1.0	1.0
4000 Series Raceway	0.8	0.9	1.0	1.0	1.0	0.8

Registration number: LGRP-02186-V01.01-EN	Drafting rules: "PEP-PCR-ed4-EN-2021 09 06" Supplemented by "PSR-0003-ed2.1-EN-2023 12 08"
Verifier accreditation number: VH43	Information and reference documents: <a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
Date of issue: 11-2025	Validity period: 5 years
Independent verification of the declaration and data in compliance with ISO 14025:2006 External <input checked="" type="checkbox"/> Internal <input type="checkbox"/>	
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDemain)	
PEP compliant with XP C08-100-1:2016 or EN 50693:2019	
The content of this PEP cannot be compared with content from any other program.	
PEP compliant with ISO 14025:2006: "Environmental labels and declarations - Type III environmental declarations"	



LCA compliant with ISO 14040:2006: "Environmental management – LCA – Principles and framework"  
LCA compliant with ISO 14044:2006: "Environmental management – LCA – Requirements and guidelines"  
Environmental data in alignment with EN 15804:2012 + A2:2019: "Sustainability of construction works - EPD's - Core rules for the product category of construction products"